



CATEGORY

WIRING & DEVICES

AMMO ITEM #

503P4W

Company: \_\_\_\_\_

Job: \_\_\_\_\_ #Item: \_\_\_\_\_

Notes: \_\_\_\_\_

# Industrial Receptacle



## SPECIFICATIONS

- Color: \_\_\_\_\_ Black
- Rating: \_\_\_\_\_ 50A, 250VAC
- NEMA: \_\_\_\_\_ 14-50R
- Pole: \_\_\_\_\_ 3
- Wire: \_\_\_\_\_ 4
- Termination: \_\_\_\_\_ Back
- Dielectric Voltage: \_\_\_\_\_ Withstands 2000V per UL498
- Face Material: \_\_\_\_\_ Thermoplastic PA
- Body Material: \_\_\_\_\_ Thermoplastic PA

## MATERIAL CHARACTERISTICS

- Environmental: Flammability, UL-94, Rated V0
- Operating Temperature: -40° F to 167° F (-40° C to 75° C)

## FEATURES

- Made of durable thermoplastic
- Heavy-gauge, double-wipe copper alloy contacts
- Easy-to-wire terminals accept up to No. 4 AWG conductors
- Terminals marked for easy identification and fast wiring
- All mounting hardware included
- Flush-mount devices fit single or two-gang outlet boxes

## PACKAGING

- Weight: \_\_\_\_\_ 335 g
- Inner: \_\_\_\_\_ 10
- Master: \_\_\_\_\_ 100
- UPC Number: \_\_\_\_\_ 83765410503



## WIRING & DEVICES



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302  
 PHONE : (718).338.1851 FAX : (718).228.1851  
 orders@ammoelectric.com

www.ammoelectric.com