



CATEGORY

WIRING &
DEVICES

AMMO ITEM #

503P4WSF

Company: _____

Job: _____ #Item: _____

Notes: _____

Industrial Receptacle



SPECIFICATIONS

- Color: _____ Black
- Rating: _____ 50A, 125/250VAC
- NEMA: _____ 14-50R
- Pole: _____ 3
- Wire: _____ 4
- Termination: _____ Back
- Dielectric Voltage: _____ Withstands 2000V per UL498
- Face Material: _____ Thermoplastic PA
- Body Material: _____ Thermoplastic PA

MATERIAL CHARACTERISTICS

- Environmental: Flammability, UL-94, Rated V0
- Operating Temperature: -40° F to 167° F (-40° C to 75° C)

FEATURES

- Made of durable thermoplastic
- Heavy-gauge, double-wipe copper alloy contacts
- Easy-to-wire terminals accept up to No. 4 AWG conductors
- Terminals marked for easy identification and fast wiring
- All mounting hardware included
- Flush-mount devices fit single or two-gang outlet boxes

PACKAGING

- Weight: _____ 158 g
- Inner: _____ 10
- Master: _____ 100
- UPC Number: _____ 837654105092



WIRING & DEVICES



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302
PHONE : (718).338.1851 FAX : (718).228.1851
orders@ammoelectric.com

www.ammoelectric.com