



CATEGORY

NEC (Nipples,
Elbows & Couplings)

AMMO ITEM #

ARALU-22

Company: _____
 Job: _____ #Item: _____
 Notes: _____

Rigid 22.5° Aluminum Elbow



APPLICATION

For use in harsh or clean environments such as waste - water treatment, food processing, oil refineries, paper mills, and powerplants

FEATURES


- Manufactured from 6063 aluminum alloy for lightweight and corrosion resistant protection
- Available from 1-1/4" thru 4"
- NPT threads are protected with color coded threaded end caps

MATERIAL

AL6063

CERTIFICATION

Standard: UL 6A ANSI C80.5



AMMO#	SIZE	A (in)	B (in)	C (in)	OD (in)	THICKNESS T (in)	STRAIGHT LENGTH L (in)	RADIUS R (in)	WEIGHT (g)	PKG	UPC
ARALU-12522	1-1/4"	8.677	1.726	8.8747	1.660	0.130	3.233	7.250	256	20	837654113786
ARALU-15022	1-1/2"	9.383	1.867	9.567	1.900	0.134	3.425	8.250	352	15	837654113790
ARALU-20022	2"	11.436	2.275	11.661	2.375	1.142	4.291	9.500	561	10	837654113806
ARALU-25022	2-1/2"	13.769	2.739	14.038	2.875	0.185	5.354	10.500	1009	50	837654113813
ARALU-30022	3"	16.841	3.350	17.171	3.500	0.197	6.516	13.000	1469	35	837654113820
ARALU-35022	3-1/2"	18.307	3.642	18.666	4.000	0.207	6.930	15.000	2126	35	837654113837
ARALU-40022	4"	18.897	3.759	19.267	4.500	0.217	7.087	16.000	2661	35	837654113844

NEC (Nipples, Elbows & Couplings)



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302
 PHONE : (718).338.1851 FAX : (718).228.1851
 orders@ammoelectric.com

www.ammoelectric.com