



CATEGORY
**ELECTRICAL
FITTINGS**

AMMO ITEM #

ARCCPLT
38-200

Company: _____

Job: _____ #Item: _____

Notes: _____

Liquidtight To Rigid Combination Coupling



Combination Coupling - Rigid or IMC to Liquidtight Conduit

APPLICATIONS

- Used to join threaded Rigid conduit or IMC to liquid tight metallic conduit (LFMC)
- Liquid-tight rated

FEATURES


- Connectors have a unique long ferrule with more pronounced threads that provide maximum surface contact for better sealing and a continuous, permanent, positive metal-to-metal ground
- Liquidtight / raintight / oiltight / concretetight
- Suitable for wet locations
- Full, machined tapered threads (NPT)

MATERIALS

- Body: zinc plated steel
- Gland: PE
- Compression Nut: zinc plated steel
- Ferrule: zinc plated steel

CERTIFICATIONS

- UL File No.E307843
- UL-514B
- CSA Standard C22.2 No. 18.3-12



AMMO#	SIZE	A (in)	B (in)	WEIGHT (kg)	INNER	MASTER	UPC
ARCCPLT-38	3/8"	1.10	1.78	70.9	20	200	837654109564
ARCCPLT-50	1/2"	1.17	1.78	64.9	20	200	837654109571
ARCCPLT-75	3/4"	1.43	1.94	99.4	10	100	837654109588
ARCCPLT-100	1"	1.76	2.19	166.2	5	50	837654109595
ARCCPLT-125	1-1/4"	2.16	2.23	244.5	5	50	837654109601
ARCCPLT-150	1-1/2"	2.38	2.62	291.4	-	12	837654109618
ARCCPLT-200	2"	2.87	2.67	406.2	-	5	837654109625

ELECTRICAL FITTINGS



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302
PHONE : (718).338.1851 FAX : (718).228.1851
orders@ammoelectric.com

www.ammoelectric.com