



CATEGORY
**ELECTRICAL
FITTINGS**

AMMO ITEM #

ARFCN90

Company: _____

Job: _____ #Item: _____

Notes: _____

Flex Metal 90° Connector



APPLICATIONS

To make a 90° termination of conduit or cable to a knockout or unthreaded slip hole in a dry location box or enclosure

FEATURES

- Male hub threads NPS
- Available with insulated throat
- Furnished with locknuts
- Combination head screws

MATERIAL


- Body: zinc die cast
- Cover: zinc plated steel

CERTIFICATIONS

- UL Standard: 514B
- CSA Standard: C22.2 No. 18

FINISH

Polishing



AMMO#	SIZE	A (in)	B (in)	C (in)	SCREWS	WEIGHT (g)	INNER	MASTER	UPC
ARFCN90-38	3/8"	1.74	.43	.37	2	40.8	50	500	837654065303
ARFCN90-50	1/2"	2.11	.64	.40	2	63.5	25	250	837654065310
ARFCN90-75	3/4"	2.40	.76	.40	2	90.7	10	100	837654065327
ARFCN90-100	1"	2.87	1.09	.54	2	172.3	5	50	837654065334
ARFCN90-125	1-1/4"	4.00	1.34	.64	2	226.7	10	40	837654065341
ARFCN90-150	1-1/2"	6.00	1.65	.75	2	453.5	-	5	837654065358
ARFCN90-200	2"	6.00	1.54	.74	2	544.3	-	5	837654065365
ARFCN90-250	2-1/2"	7.18	2.45	.87	4	1632.9	-	5	837654068632
ARFCN90-300	3"	7.87	2.93	1.03	4	2041.1	-	2	837654068649
ARFCN90-350	3-1/2"	9.40	3.28	1.03	4	4082.3	-	1	837654068656
ARFCN90-400	4"	10.20	3.68	1.03	4	4535.9	-	1	837654068663

ELECTRICAL FITTINGS



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302
PHONE : (718).338.1851 FAX : (718).228.1851
orders@ammoelectric.com

www.ammoelectric.com