



CATEGORY
**ELECTRICAL
 FITTINGS**
 AMMO ITEM #
ARFCNS

Company: _____
 Job: _____ #Item: _____
 Notes: _____

FX AC MC Straight Connector Squeeze-Zinc



APPLICATION

These squeeze type connectors are used to terminate flexible metal conduit to a knockout in a dry location box or enclosure

FEATURES

- Male hub threads NPS
- Available with insulated throat
- Furnished with locknuts
- Combination head screws

MATERIAL

- Body: Zinc die cast
- Locknut: Zinc die cast

CERTIFICATIONS

- UL Standard: 514B
- CSA Standard: C22.2 No. 18



AMMO#	SIZE	WEIGHT (g)	INNER	MASTER	UPC
ARFCNS-38	3/8"	22.7	50	500	837654065211
ARFCNS-50	1/2"	30.9	25	250	837654065228
ARFCNS-75	3/4"	41.2	25	250	837654065235
ARFCNS-100	1"	66.8	10	100	837654065242
ARFCNS-125	1-1/4"	71.6	10	100	837654065259
ARFCNS-150	1-1/2"	127.0	5	50	837654065266
ARFCNS-200	2"	185.8	10	40	837654065273
ARFCNS-250	2-1/2"	360	-	10	837654065280
ARFCNS-300	3"	440	-	10	837654065297
ARFCNS-350	3-1/2"	505	-	1	837654068557
ARFCNS-400	4"	750	-	1	837654068564

ELECTRICAL FITTINGS



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302
 PHONE : (718).338.1851 FAX : (718).228.1851
 orders@ammoelectric.com

www.ammoelectric.com