



CATEGORY
**ELECTRICAL
FITTINGS**

AMMO ITEM #

ARGBU-MHDG

Company: _____

Job: _____ #Item: _____

Notes: _____

Insulated Metallic Grounding Bushings



FEATURES

- Hot dip galvanized for superior protection against corrosion
- Tin plated aluminum alloy 6061-T6 rated for AL and CU conductor
- Liner is rated flame retardant to 105°C
- UL listed for use with copper or aluminum grounding conductor

MATERIALS

- Body - Malleable iron
- Plastic insulator
- Lug - Aluminum
- Clamping screw - Steel
- Set screws - Steel

FINISH


Hot dip galvanized

CERTIFICATIONS

- UL Standard: UL 514B and UL 467
- RoHS
- Fed. Spec: A-A-50553
- NEMA: FB 1

APPLICATIONS

- Use to provide a means of grounding Rigid or IMC conduit
- Indoor or outdoor use (aluminum lug)
- Use with locknut to terminate service conduit to a cabinet
- Lug provided for bonding jumper to a neutral bus bar
- Round surface of bushing prevents damage to wire insulation
- Plastic liner prevents damage to wire insulation



AMMO#	SIZE	MIN.	MAX.	A (in)	B (in)	WEIGHT/ CASE (Lbs)	WEIGHT (g)	INNER	MASTER	UPC
ARGBU-50MHDG	1/2"	14	4	1.08	.57	45	136	50	500	837654112113
ARGBU-75MHDG	3/4"	14	4	1.31	.57	50	186	50	500	837654112120
ARGBU-100MHDG	1"	14	4	1.61	.65	32	264	25	250	837654112137
ARGBU-125MHDG	1-1/4"	14	4	1.91	.71	36	260	20	200	837654112144
ARGBU-150MHDG	1-1/2"	14	4	2.16	.73	25	300	10	100	837654112151
ARGBU-200MHDG	2"	14	4	2.72	.73	30	390	10	100	837654112168
ARGBU-250MHDG	2-1/2"	14	1/0	3.23	.94	25	700	5	50	837654112175
ARGBU-300MHDG	3"	14	1/0	3.88	.94	18	1296	---	25	837654112182
ARGBU-350MHDG	3-1/2"	14	1/0	4.43	.94	20	3600	---	10	837654112199
ARGBU-400MHDG	4"	14	1/0	4.89	.94	2	4320	---	10	837654112205

ELECTRICAL FITTINGS



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302
PHONE : (718).338.1851 FAX : (718).228.1851
orders@ammoelectric.com

www.ammoelectric.com