



CATEGORY  
**ELECTRICAL  
 FITTINGS**  
 AMMO ITEM #  
**ARGWTH**

Company: \_\_\_\_\_  
 Job: \_\_\_\_\_ #Item: \_\_\_\_\_  
 Notes: \_\_\_\_\_

# Watertight Hubs Insulated Die Cast Zinc



### APPLICATIONS

- Used to connect rigid metal conduit or IMC to a threadless opening in an enclosure
- May be used in wet or dry locations, indoors or outdoors

### FEATURES

- Rugged metallic construction ensures mechanical protection
- Insulated throat, rated up to 105 °C, prevents wire abrasion
- Integral O-ring provides watertight seal
- Grounding version provides positive ground for external conductor
- Unique profile permits easy wrenching
- Smooth, accurately tapped threads facilitate installation
- Watertight and corrosion resistant
- NEMA Types 2, 3, 3R, 4, 4X, 5, 12, 13



### MATERIAL

- Bodies and nuts: Zinc die cast
- O-ring: BUNA-N
- Insulator: polypropylene
- Ground screw: stainless steel

### CERTIFICATIONS

- UL Standard: 514B
- CSA Standard: C22.2 No. 18.3
- NEMA: FB-1

AMMO#	SIZE	WEIGHT (g)	INNER	MASTER	UPC
ARGWTH-50	1/2"	62	25	250	837654103968
ARGWTH-75	3/4"	85	10	100	837654103975
ARGWTH-100	1"	124	10	100	837654103982
ARGWTH-125	1 1/4"	224	2	20	837654103999
ARGWTH-150	1 1/2"	298	2	20	837654104002
ARGWTH-200	2"	326	2	20	837654104019
ARGWTH-250	2 1/2"	492	2	2	837654104026
ARGWTH-300	3"	838	-	2	837654104033
ARGWTH-350	3 1/2"	750	-	1	837654104040
ARGWTH-400	4"	930	-	1	837654104057

## ELECTRICAL FITTINGS



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302  
 PHONE : (718).338.1851 FAX : (718).228.1851  
 orders@ammoelectric.com

www.ammoelectric.com