



CATEGORY
**ELECTRICAL
FITTINGS**

AMMO ITEM #

ARHBT

Company: _____
Job: _____ #Item: _____
Notes: _____

Black Cable Tie with Hole



Nylon cable ties with mountable head

APPLICATION

Wrap the cable and fix with screw

FEATURES

- Operation temperature -40° F to +185° F
- Minimum installation temperature 14° F
- UL94 V-2 flammability, and UV resistant

MATERIAL

Nylon PA66

CERTIFICATIONS

- Rohs
- UL



AMMO#	SIZE (in)	SCREW HOLE SIZE	TENSILE STRENGTH	MIN / MAX BUNDLE DIAMETER	WEIGHT (g)	PKG	UPC
ARHBT04-100	4 x 0.984	3.30 - 3.50 mm	80N	3.0 - 19.0 mm	0.40	100	837654113127
ARHBT04-1000	4 x 0.984	3.30 - 3.50 mm	80N	3.0 - 19.0 mm	0.40	1000	837654113134
ARHBT05-100	5 x 1.417	3.40 - 3.60 mm	180N	3.0 - 35.5 mm	0.80	100	837654113141
ARHBT05-1000	5 x 1.417	3.40 - 3.60 mm	180N	3.0 - 35.5 mm	0.80	1000	837654113158
ARHBT07-100	7 x 0.181	3.96 - 4.16 mm	222N	3.0 - 36.8 mm	1.10	100	837654113165
ARHBT07-1000	7 x 0.181	3.96 - 4.16 mm	222N	3.0 - 36.8 mm	1.10	1000	837654113172
ARHBT08-100	8 x 0.181	3.96 - 4.16 mm	222N	3.0 - 49.8 mm	1.30	100	837654113189
ARHBT08-1000	8 x 0.181	3.96 - 4.16 mm	222N	3.0 - 49.8 mm	1.30	1000	837654113196
ARHBT11-100	11 x 0.181	3.96 - 4.16 mm	222N	3.0 - 82.8 mm	1.93	100	837654113202
ARHBT11-1000	11 x 0.181	3.96 - 4.16 mm	222N	3.0 - 82.8 mm	1.93	1000	837654113219
ARHBT14-100	14 x 0.181	3.96 - 4.16 mm	222N	3.0 - 103.8 mm	2.39	100	837654113226
ARHBT14-1000	14 x 0.181	3.96 - 4.16 mm	222N	3.0 - 103.8 mm	2.39	1000	837654113233
ARHBT18-100	18 x 2.992	5.36 - 5.59 mm	540N	8.0 - 109.2 mm	6.97	100	837654113240
ARHBT18-1000	18 x 2.992	5.36 - 5.59 mm	540N	8.0 - 109.2 mm	6.97	1000	837654113257

ELECTRICAL FITTINGS



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302
PHONE : (718).338.1851 FAX : (718).228.1851
orders@ammoelectric.com

www.ammoelectric.com