



CATEGORY
**ELECTRICAL
FITTINGS**

AMMO ITEM #

**ARLNS
50-400**

Company: _____

Job: _____ #Item: _____

Notes: _____

Steel Locknuts



Used to secure threaded conduits or connectors to electrical junction boxes

APPLICATIONS

- Insulated zinc die casting grounding bushings are used on the end of rigid and IMC conduits and other threaded connectors to provide a smooth well rounded bearing surface to protect wires or cables
- Providing a means to connect a grounding conductor
- Nylon Liner Rated 150° C

FEATURE


Use for IMC/ Rigid conduit

MATERIAL/FINISH

- Zinc plated steel
- Electro-Gal

CERTIFICATIONS

- UL Standard: 514B
- CSA Standard: C22.2 No. 18



AMMO#	SIZE	THREAD PITCH DIAMETER	A (in)	B (in)	WEIGHT (g)	INNER	MASTER	UPC
ARLNS-50	1/2"	.787 - .797	1.15	.11	4.1	100	2000	837654065686
ARLNS-75	3/4"	.999 - 1.009	1.45	.115	5.8	100	1000	837654065693
ARLNS-100	1"	1.25 - 1.26	1.75	.14	10.5	100	1000	837654065709
ARLNS-125	1-1/4"	1.595 - 1.605	2.10	.14	18.1	50	500	837654065716
ARLNS-150	1-1/2"	1.837 - 1.847	2.40	.14	21.0	50	500	837654065723
ARLNS-200	2"	2.307 - 2.317	2.95	.14	28.0	25	250	837654065730
ARLNS-250	2-1/2"	2.777 - 2.788	3.55	.185	61.3	-	50	837654065747
ARLNS-300	3"	3.403 - 3.414	3.55	.19	83.0	-	50	837654065754
ARLNS-350	3-1/2"	3.892 - 3.904	4.20	.19	108.8	-	25	837654071106
ARLNS-400	4"	4.399 - 4.411	4.75	.19	453.5	-	25	837654065761

ELECTRICAL FITTINGS



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302
PHONE : (718).338.1851 FAX : (718).228.1851
orders@ammoelectric.com

www.ammoelectric.com