



CATEGORY  
**ELECTRICAL  
FITTINGS**

AMMO ITEM #

**ARLTCN**  
38MI-400MI

Company: \_\_\_\_\_

Job: \_\_\_\_\_ #Item: \_\_\_\_\_

Notes: \_\_\_\_\_

# Liquid Tight Straight Connector

## Malleable Iron



### APPLICATIONS

- To secure, ground and seal liquid-tight flexible metal conduit to boxes and enclosures
- Connects conduit and terminates bonding conductor run externally across liquid-tight conduit

### FEATURES

- Tapered threaded male hub NPT
- Compact, slim diameter with small turning radius
- Furnished with an insulated throat with steel locknut and sealing ring
- Suitable for wet locations
- Long ferrule prevents pullout and tight bend conduit "pop-out"
- RoHS compliant

### MATERIALS



- Malleable iron
- Steel locknut

### FINISHES

- Malleable iron - electro zinc plated and chromate coated
- Steel - electro zinc plated and chromate coated
- PE, PP, Alum - natural

### CERTIFICATIONS

- UL Standards: 514B
- CUL Standard: C22.2 No.18.3-12
- Fed. Spec. W-F-408E
- NEMA: FB-1



AMMO#	SIZE	A (in)	B (in)	C (in)	WEIGHT (g)	INNER	MASTER	UPC
ARLTCN-38MI	3/8"	0.917	0.531	1.220	72	20	200	837654104064
ARLTCN-50MI	1/2"	0.925	0.535	1.339	78	20	200	837654104071
ARLTCN-75MI	3/4"	1.008	0.591	1.602	109	10	100	837654104088
ARLTCN-100MI	1"	1.083	0.543	1.795	171	5	50	837654104095
ARLTCN-125MI	1-1/4"	1.224	0.673	2.402	247	5	50	837654104101
ARLTCN-150MI	1-1/2"	1.244	0.701	2.638	362	2	20	837654104118
ARLTCN-200MI	2"	1.453	0.709	3.181	495	2	20	837654104125
ARLTCN-250MI	2-1/2"	1.929	1.087	3.843	974	-	1	837654104132
ARLTCN-300MI	3"	2.079	1.114	4.701	1424	-	1	837654104149
ARLTCN-350MI	3-1/2"	2.031	1.134	5.252	1787	-	1	837654104156
ARLTCN-400MI	4"	2.228	1.150	6.472	2170	-	1	837654104163

## ELECTRICAL FITTINGS



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302  
PHONE : (718).338.1851 FAX : (718).228.1851  
orders@ammoelectric.com

www.ammoelectric.com