



CATEGORY  
**ELECTRICAL  
FITTINGS**

AMMO ITEM #

ARLTCN  
38I-200I

Company: \_\_\_\_\_

Job: \_\_\_\_\_ #Item: \_\_\_\_\_

Notes: \_\_\_\_\_

# Straight Liquid Tight Connector Insulated



## APPLICATIONS

- To secure, ground and seal liquid-tight flexible metal conduit to boxes and enclosures
- Connects conduit and terminates bonding conductor run externally across liquid-tight conduit

## FEATURES

- Tapered threaded male hub NPT
- Compact, slim diameter with small turning radius
- Furnished with an insulated throat with steel locknut and sealing ring
- Suitable for wet locations
- Long ferrule prevents pullout and tight bend conduit "pop-out"
- RoHS compliant

## MATERIAL


Steel locknut

## FINISHES

- Electro zinc plated and chromate coated
- Steel - electro zinc plated and chromate coated
- PE, PP, Alum - natural

## CERTIFICATIONS

- UL Standards: 514B
- CUL Standard: C22.2 No.18.3-12
- Fed. Spec. W-F-408E
- NEMA: FB-1



AMMO#	SIZE	A (in)	B (in)	C (in)	WEIGHT (g)	INNER	MASTER	UPC
ARLTCN-38I	3/8 1/2" KO	0.917	0.531	1.220	49.0	20	200	837654068410
ARLTCN-50I	1/2"	0.925	0.535	1.339	53.0	20	200	837654068427
ARLTCN-75I	3/4"	1.008	0.591	1.602	70.0	10	100	837654068434
ARLTCN-100I	1"	1.083	0.543	1.795	106.0	5	50	837654068441
ARLTCN-125I	1-1/4"	1.224	0.673	2.402	199.0	5	50	837654068458
ARLTCN-150I	1-1/2"	1.244	0.701	2.638	236.5	2	20	837654068465
ARLTCN-200I	2"	1.453	0.709	3.181	300.8	2	20	837654068472

## ELECTRICAL FITTINGS



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302  
PHONE : (718).338.1851 FAX : (718).228.1851  
orders@ammoelectric.com

www.ammoelectric.com