



CATEGORY

**ELECTRICAL
FITTINGS**

AMMO ITEM #

ARLTCN-MI

Company: _____

Job: _____ #Item: _____

Notes: _____

Liquid Tight Straight Connector Malleable Iron



APPLICATIONS

- To secure, ground and seal liquid-tight flexible metal conduit to boxes and enclosures
- Connects conduit and terminates bonding conductor run externally across liquid-tight conduit

FEATURES

- Tapered threaded male hub NPT
- Compact, slim diameter with small turning radius
- Furnished with an insulated throat with steel locknut and sealing ring
- Suitable for wet locations
- Long ferrule prevents pullout and tight bend conduit "pop-out"
- RoHS compliant

MATERIALS



- Malleable iron
- Steel locknut

CERTIFICATIONS

- UL Standards: 514B
- CUL Standard: C22.2 No.18.3-12
- Fed. Spec. W-F-408E
- NEMA: FB-1

FINISHES

- Malleable iron - electro zinc plated and chromate coated
- Steel - electro zinc plated and chromate coated
- PE, PP, Alum - natural



AMMO#	SIZE	A (in)	B (in)	C (in)	WEIGHT (lb)	INNER	MASTER	UPC
ARLTCN-38MI	3/8"	0.917	0.531	1.220	0.16	20	200	840526220960
ARLTCN-50MI	1/2"	0.925	0.535	1.339	0.17	20	200	840526220977
ARLTCN-75MI	3/4"	1.008	0.591	1.602	0.24	10	100	840526220984
ARLTCN-100MI	1"	1.083	0.543	1.795	0.38	5	50	840526220991
ARLTCN-125MI	1-1/4"	1.224	0.673	2.402	0.54	5	50	840526221004
ARLTCN-150MI	1-1/2"	1.244	0.701	2.638	0.80	2	20	840526221011
ARLTCN-200MI	2"	1.453	0.709	3.181	1.09	2	20	840526221028
ARLTCN-250MI	2-1/2"	1.929	1.087	3.843	2.15	-	1	840526221035
ARLTCN-300MI	3"	2.079	1.114	4.701	3.14	-	1	840526221042
ARLTCN-350MI	3-1/2"	2.031	1.134	5.252	3.94	-	1	840526221059
ARLTCN-400MI	4"	2.228	1.150	6.472	4.78	-	1	840526221066

ELECTRICAL FITTINGS



1000 COMMERCE CENTER DR ELKTON MD 21921
 PHONE : (718).338.1851 FAX : (718).228.1851
 orders@ammoelectric.com

www.ammoelectric.com