



CATEGORY
**ELECTRICAL
 FITTINGS**
 AMMO ITEM #
ARLTCN

Company: _____
 Job: _____ #Item: _____
 Notes: _____

Straight Liquid Tight Connector



APPLICATIONS

- To secure, ground and seal liquid-tight flexible metal conduit to boxes and enclosures
- Connects conduit and terminates bonding conductor run externally across liquid-tight conduit

FEATURES

- Tapered threaded male hub NPT
- Compact, slim diameter with small turning radius
- Furnished with an insulated throat with steel locknut and sealing ring
- Suitable for wet locations
- Long ferrule prevents pullout and tight bend conduit "pop-out"
- RoHS compliant

MATERIAL


Steel locknut

FINISHES

- Electro zinc plated and chromate coated
- Steel - electro zinc plated and chromate coated
- PE, PP, Alum - natural

CERTIFICATIONS

- UL Standards: 514B
- CUL Standard: C22.2 No.18.3-12
- Fed. Spec. W-F-408E
- NEMA: FB-1



AMMO#	SIZE	A (in)	B (in)	C (in)	WEIGHT (g)	INNER	MASTER	UPC
ARLTCN-50	1/2"	0.925	0.535	1.339	52.6	20	200	837654065419
ARLTCN-75	3/4"	1.008	0.591	1.602	69.0	10	100	837654065426
ARLTCN-100	1"	1.083	0.543	1.795	105.0	5	50	837654065433
ARLTCN-125	1-1/4"	1.224	0.673	2.402	197.0	5	50	837654065440
ARLTCN-150	1-1/2"	1.244	0.701	2.638	234.5	2	20	837654065457
ARLTCN-200	2"	1.453	0.709	3.181	298.0	2	20	837654065464
ARLTCN-250	2-1/2"	1.929	1.087	3.843	686.0	-	1	837654065471
ARLTCN-300	3"	2.079	1.114	4.701	998.0	-	1	837654065488
ARLTCN-350	3-1/2"	2.031	1.134	5.252	1062.0	-	1	837654068403
ARLTCN-400	4"	2.228	1.150	6.472	1365.5	-	1	837654065495

ELECTRICAL FITTINGS



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302
 PHONE : (718).338.1851 FAX : (718).228.1851
 orders@ammoelectric.com

www.ammoelectric.com