



CATEGORY
**ELECTRICAL
FITTINGS**

AMMO ITEM #

ARLTCN90
50-400

Company: _____

Job: _____ #Item: _____

Notes: _____

Liquid Tight 90° Connector



APPLICATIONS

- To secure, ground and seal liquid-tight flexible metal conduit to boxes and enclosures
- Connects conduit and terminates bonding conductor run externally across liquid-tight conduit

FEATURES

- Tapered threaded male hub NPT
- Compact, slim diameter with small turning radius
- Furnished with an insulated throat with steel locknut and sealing ring
- Suitable for wet locations
- Long ferrule prevents pullout and tight bend conduit "pop-out"
- RoHS compliant

MATERIAL


Steel locknut

FINISHES

- Electro zinc plated and chromate coated
- Steel - electro zinc plated and chromate coated
- PE, PP, Alum - natural

CERTIFICATIONS

- UL Standards: 514B
- CUL Standard: C22.2 No.18.3-12
- Fed. Spec. W-F-408E
- NEMA: FB-1



AMMO#	SIZE	A (in)	B (in)	C (in)	WEIGHT (g)	INNER	MASTER	UPC
ARLTCN90-50	1/2"	2.749	0.543	1.241	83.5	25	250	837654065501
ARLTCN90-75	3/4"	2.977	0.580	1.503	104.6	10	100	837654065518
ARLTCN90-100	1"	3.644	0.675	1.763	184.8	5	50	837654065525
ARLTCN90-125	1-1/4"	4.138	0.695	2.248	296.4	2	20	837654065532
ARLTCN90-150	1-1/2"	4.635	0.694	2.471	372.0	2	20	837654065549
ARLTCN90-200	2"	5.347	0.729	3.007	499.0	1	10	837654065556
ARLTCN90-250	2-1/2"	8.217	1.056	3.654	954.0	-	1	837654065563
ARLTCN90-300	3"	9.18	1.104	4.471	1361.0	-	1	837654065570
ARLTCN90-350	3-1/2"	9.871	1.163	4.942	1675.0	-	1	837654068489
ARLTCN90-400	4"	10.757	1.155	5.501	2114.0	-	1	837654065587

ELECTRICAL FITTINGS



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302
PHONE : (718).338.1851 FAX : (718).228.1851
orders@ammoelectric.com

www.ammoelectric.com