



CATEGORY
**ELECTRICAL
FITTINGS**

AMMO ITEM #

ARLTGN45
38MI-400MI


Company: _____

Job: _____ #Item: _____

Notes: _____



Liquid Tight 45° Ground Connector Malleable Iron



APPLICATIONS

- To secure, ground and seal liquid-tight flexible metal conduit to boxes and enclosures
- Connects conduit and terminates bonding conductor run externally across liquid-tight conduit

FEATURES

- Tapered threaded male hub NPT
- Compact, slim diameter with small turning radius
- Furnished with an insulated throat with steel locknut and sealing ring
- Suitable for wet locations
- Long ferrule prevents pullout and tight bend conduit "pop-out"
- RoHS compliant

MATERIALS

- Malleable iron
- Steel locknut

FINISHES

- Malleable iron - electro zinc plated and chromate coated
- Steel - electro zinc plated and chromate coated
- PE, PP, Alum - natural

CERTIFICATIONS

- UL Standards: 514B
- CUL Standard: C22.2 No.18.3-12
- Fed. Spec. W-F-408E
- NEMA: FB-1

AMMO#	SIZE	A (in)	B (in)	C (in)	LUG SIZE	WEIGHT (kg)	INNER	MASTER	UPC
ARLTGN45-38MI	3/8"	2.071	0.536	1.120	4 - 14	0.180	5	50	837654104392
ARLTGN45-50MI	1/2"	2.071	0.543	1.241	4 - 14	0.200	5	50	837654104408
ARLTGN45-75MI	3/4"	2.341	0.580	1.503	4 - 14	0.250	5	50	837654104415
ARLTGN45-100MI	1"	2.836	0.675	1.763	4 - 14	0.320	2	20	837654104422
ARLTGN45-125MI	1-1/4"	3.388	0.695	2.248	4 - 14	0.500	2	20	837654104439
ARLTGN45-150MI	1-1/2"	3.447	0.694	2.471	4 - 14	0.800	2	20	837654104446
ARLTGN45-200MI	2"	4.178	0.729	3.007	4 - 14	0.800	2	20	837654104453
ARLTGN45-250MI	2 -1/2"	6.109	1.056	3.654	1/0 - 8	1.750	-	1	837654104460
ARLTGN45-300MI	3"	6.588	1.104	4.471	1/0 - 8	2.500	-	1	837654104477
ARLTGN45-350MI	3-1/2"	7.022	1.163	4.942	3/0 - 6	3.500	-	1	837654104484
ARLTGN45-400MI	4"	7.848	1.155	5.501	3/0 - 6	4.000	-	1	837654104491

ELECTRICAL FITTINGS



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302
PHONE : (718).338.1851 FAX : (718).228.1851
orders@ammoelectric.com

www.ammoelectric.com