



CATEGORY

**NEC (Nipples,
Elbows & Couplings)**

AMMO ITEM #

**ARRP
01-10**

Company: _____

Job: _____ #Item: _____

Notes: _____

Rigid Compression Coupling Steel



ARRP Series Rigid Conduit and IMC Coupling are used to joint two length of Rigid Conduit or IMC. Concrete tight

FEATURES



- Used to join unthreaded rigid conduit or IMC to box or enclosure
- Optional insulator available to protect cable from potential damage
- Concrete Tight

MATERIALS / FINISHES

- Body / Gland Nut: Steel / Zinc Plated
- Locknut: Steel / Zinc Plated

COMPLIANCES AND CERTIFICATIONS

- UL File No.E477232
- UL-514B
- Federal Specification A-A-50553
- CSA Standard C22.2 18.3-04
- NEMA FB-1



AMMO#	SIZE	A (in)	B (in)	WEIGHT (g)	INNER	MASTER	UPC
ARRP01	1/2"	1.18"	1.72"	69.3	10	100	837654085813
ARRP02	3/4"	1.42"	1.99"	109.0	10	100	837654085820
ARRP03	1"	1.76"	2.22"	172.3	5	50	837654085837
ARRP04	1-1/4"	2.16"	2.48"	282.0	5	50	837654085844
ARRP05	1-1/2"	2.38"	2.56"	327.0	-	12	837654085851
ARRP06	2"	3.38"	2.62"	413.0	-	12	837654085868
ARRP07	2-1/2"	3.75"	4.86"	825.0	-	5	837654085875
ARRP08	3"	4.25"	5.72"	890.0	-	3	837654085882
ARRP09	3-1/2"	4.75"	6.00"	1050.0	-	2	837654085899
ARRP10	4"	5.31"	6.81"	1215.0	-	2	837654085905

NEC (Nipples, Elbows & Couplings)



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302
PHONE : (718).338.1851 FAX : (718).228.1851
orders@ammoelectric.com

www.ammoelectric.com