



CATEGORY
**ELECTRICAL
FITTINGS**

AMMO ITEM #

**ARSCNZ
50-400**

Company: _____
Job: _____ #Item: _____
Notes: _____

Connector Set Screw



APPLICATION

Set screw type EMT tubing connectors are used to secure and terminate steel EMT conduit to knock-outs in concrete tight to the steel outlet box or dry or wet location applications

FEATURES

- Set screw type connectors
- Concrete tight when taped
- Assembled with a die cast locknut

MATERIAL / FINISH

- Zinc die casting
- Polishing



AMMO#	TRADE SIZE	METRIC DESIGNATOR	HIGHT	INSIDE DIAMETER	OUTSIDE DIAMETER	WALL THICK	WEIGHT (g)	PKG	UPC
ARSCNZ-50	1/2"	16	27.23 mm	18.33 mm	22.00 mm	1.00 mm	18.18	500	837654067536
ARSCNZ-75	3/4"	21	33.20 mm	23.80 mm	25.81 mm	1.00 mm	28.84	250	837654067543
ARSCNZ-100	1"	27	36.67 mm	30.11 mm	34.80 mm	1.00 mm	42.90	200	837654067550
ARSCNZ-125	1-1/4"	35	47.79 mm	38.80 mm	45.72 mm	1.46 mm	83.60	25	837654067567
ARSCNZ-150	1-1/2"	41	51.60 mm	44.78 mm	51.95 mm	1.57 mm	102.00	25	837654067574
ARSCNZ-200	2"	53	59.80 mm	56.26 mm	60.45 mm	2.00 mm	164.50	20	837654067581
ARSCNZ-250	2-1/2"	63	78.20 mm	74.02 mm	80.03 mm	3.00 mm	380.00	12	837654067598
ARSCNZ-300	3"	78	85.10 mm	90.58 mm	98.93 mm	3.00 mm	455.83	12	837654067604
ARSCNZ-350	3-1/2"	91	87.88 mm	102.30 mm	108.50 mm	3.20 mm	592.00	10	837654071267
ARSCNZ-400	4"	103	95.25 mm	115.9 mm 1	124.19 mm	3.20 mm	535.00	6	837654067611

ELECTRICAL FITTINGS



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302
PHONE : (718).338.1851 FAX : (718).228.1851
orders@ammoelectric.com

www.ammoelectric.com