



CATEGORY  
**ELECTRICAL  
FITTINGS**

AMMO ITEM #

ARSCNZ  
50I-400I

Company: \_\_\_\_\_

Job: \_\_\_\_\_ #Item: \_\_\_\_\_

Notes: \_\_\_\_\_

# Connector Set Screw Insulated



## APPLICATION

Set screw type EMT tubing connectors are used to secure and terminate steel EMT conduit to knock-outs in concrete tight to the steel outlet box or dry or wet location applications

## FEATURES

- Set screw type connectors
- Concrete tight when taped
- Assembled with a die cast locknut
- Connector available with insulated throat

## MATERIAL / FINISH

- Zinc die casting
- Polishing



AMMO#	TRADE SIZE	METRIC DESIGNATOR	HIGHT	INSIDE DIAMETER	OUTSIDE DIAMETER	WALL THICK	WEIGHT (g)	PKG	UPC
ARSCNZ-50I	1/2"	16	27.23 mm	18.33 mm	22.00 mm	1.00 mm	18.18	500	837654067628
ARSCNZ-75I	3/4"	21	33.20 mm	23.80 mm	25.81 mm	1.00 mm	28.84	250	837654067635
ARSCNZ-100I	1"	27	36.67 mm	30.11 mm	34.80 mm	1.00 mm	42.90	200	837654067642
ARSCNZ-125I	1-1/4"	35	47.79 mm	38.80 mm	45.72 mm	1.46 mm	83.60	25	837654067659
ARSCNZ-150I	1-1/2"	41	51.60 mm	44.78 mm	51.95 mm	1.57 mm	102.00	25	837654067666
ARSCNZ-200I	2"	53	59.80 mm	56.26 mm	60.45 mm	2.00 mm	164.50	20	837654067673
ARSCNZ-250I	2-1/2"	63	78.20 mm	74.02 mm	80.03 mm	3.00 mm	380.00	12	837654067680
ARSCNZ-300I	3"	78	85.10 mm	90.58 mm	98.93 mm	3.00 mm	455.83	12	837654067697
ARSCNZ-350I	3-1/2"	91	87.88 mm	102.30 mm	108.50 mm	3.20 mm	592.00	10	837654088111
ARSCNZ-400I	4"	103	95.25 mm	115.9 mm 1	124.19 mm	3.20 mm	535.00	6	837654067703

## ELECTRICAL FITTINGS



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302  
PHONE : (718).338.1851 FAX : (718).228.1851  
orders@ammoelectric.com

www.ammoelectric.com