



CATEGORY

**STRUT &
GROUND**

AMMO ITEM #

**ARSN1420-3816
1213**

Company: _____
 Job: _____ #Item: _____
 Notes: _____

SPRING NUT

FEATURES

Are designed to provide resistance to pull-out and side slip in excess of the full strength of the channels with which they are used. These nuts offer a silver electroplated finish and are designed for use with Strut Channels and inserts. Alternate teeth are spaced and designed to develop a wedging action that increases with pressure or load.

APPLICATION

During the installation process of Strut Channel and its accessories, Channel Nuts can quickly install and effectively fix other accessories.

MATERIAL

- Nut: Low carbon steel
- Spring: Spring steel



AMMO#	SIZE	LENGTH	WIDTH	THICKNESS	PULL-OUT STRENGTH (LBS)	WEIGHT (g)	PKG	UPC
ARSN1420-R	1/4"	1.358"+/-0.02"	0.748"+/-0.02"	0.230"-0.250"	450	27.5	100	83765410022
ARSN1420-S	1/4"	1.358"+/-0.02"	0.748"+/-0.02"	0.230"-0.250"	450	26.8	100	83765410023
ARSN3816-R	3/8"	1.358"+/-0.02"	0.748"+/-0.02"	0.355"-0.375"	1100	38.4	100	83765410025
ARSN3816-S	3/8"	1.358"+/-0.02"	0.748"+/-0.02"	0.355"-0.375"	1100	37.6	100	83765410024
ARSN1213-R	1/2"	1.358"+/-0.02"	0.748"+/-0.02"	0.355"-0.375"	1275	44.5	100	83765410020
ARSN1213-S	1/2"	1.358"+/-0.02"	0.748"+/-0.02"	0.462"-0.482"	1275	43.9	100	83765410021

STRUT & GROUND



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302
 PHONE : (718).338.1851 FAX : (718).228.1851
 orders@ammoelectric.com

www.ammoelectric.com