

Com	pany
Job:	

Notes:

#Item: \_\_\_\_\_

# **Rigid/IMC Combination Conduit Bodies with Covers - T Type**

#### **APPLICATIONS**

- · Act as pull outlets for conductors being installed
- Make bends and change direction for conduit system
- Provide opening for splicing
- Allow for branch connection runs
- Provide for access to conductors for future maintenance and system changes

#### **FEATURES**


- Die cast copper-free aluminum construction is lightweight and corrosion resistant for long reliable service
- Epoxy powder coat finish provides additional corrosion resistance in a good appearance
- Flat back suitable for mounting on surface
- Provide flexible choices for orders, supply with separate bodies or as assembly
- Rated for Wet Locations when used with cover and gasket to join threaded Rigid conduit

#### MATERIALS

- Body: Die Cast Aluminum
- Covers: Stamped Steel







CATEGORY

CONDUIT BODIES

**ARTC-CF** 

AMMO#	SIZE	A (In)	B (In)	C (In)	WEIGHT (g)	PKG	UPC
ARTC-50CF	1/2"	4.720	1.370	2.030	110.6	50	837654071755
ARTC-75CF	3/4"	5.570	1.625	2.335	146.6	50	837654071762
ARTC-100CF	1"	6.460	1.900	2.705	208.3	25	837654071779
ARTC-125CF	1-1/4"	8.528	2.770	3.630	436.6	10	837654071786
ARTC-150CF	1-1/2"	8.528	2.770	3.630	428.7	10	837654071793
ARTC-200CF	2"	10.831	3.335	3.980	847.5	10	837654071809

## **CONDUIT BODIES**



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302 PHONE : (718).338.1851 FAX : (718).228.1851 orders@ammoelectric.com

### www.ammoelectric.com