



CATEGORY

PVC

AMMO ITEM #

DB60-5-20-PVC

Company: \_\_\_\_\_

Job: \_\_\_\_\_ #Item: \_\_\_\_\_

Notes: \_\_\_\_\_

# 5" Rigid PVC Conduit

## Type DB 60 - 20 FT

### ENVIRONMENTAL CONDITIONS

23°C ± 2°C - 50%HR ± 5%HR

### STANDARD PARAMETERS

- Resistance to impact: \_\_\_\_\_ 1.30
- Resistance to crushing: \_\_\_\_\_ 414 kN/m<sup>2</sup>

### MATERIAL

Rigid poly (vinyl chloride) (PVC)

### PACKAGING

- Weight: \_\_\_\_\_ 17.6 kg
- PKG: \_\_\_\_\_ 1
- UPC number: \_\_\_\_\_ 837654115398



DIMENSIONS							
STANDARD PARAMETERS							
WALL THICKNESSES (mm)			OUTSIDE DIMETERS (mm)	OUT-OF-ROUNDNESS (mm)	TOLERANCE (mm)	MINIMUM AVERAGE INSIDE DIAMETER	VARIATION
MIN	NORMAL	MAX					

4.17	4.55	4.93	141.3	2.54	0.25	N/A	6%
------	------	------	-------	------	------	-----	----

HOOD DIMENSIONS (mm)						
SOCKET DIAMETERS AT ENTRANCE	TOLERANCE	OUT-OF-ROUNDNESS	SOCKET DIAMETERS AT BOTTOM	OUT-OF-ROUNDNESS	MINIMUM BELL LENGTH	MAXIMUM HOOD LEGTH

142.6	0.25	2.54	141.55	2.54	102	130
-------	------	------	--------	------	-----	-----

PVC



Ammo Electric Inc.

400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302  
 PHONE : (718).338.1851 FAX : (718).228.1851  
 orders@ammoelectric.com

www.ammoelectric.com