



CATEGORY
**ELECTRICAL
 CONDUIT & WIRES**
 AMMO ITEM #
EMT Conduit

Company: _____

Job: _____ #Item: _____

Notes: _____

EMT Conduit



EMT galvanizing process for greater protection against corrosion. Finished with durable and clear anti-corrosion coating for higher protection outside and higher grade epoxy coating inside.

AMMO#	TRADE SIZE		NOMINAL OD		WALL THICK.A		APROX 100FTAP		WEIGHT (g)	PKG		UPC
	US	METRIC	in	mm	in	mm	lbs	kg		FT	PCS	
1/2-10-EMT	1/2	16	0.706	17.93	0.042	1.07	30	13.6	1370	7000	700	837654107669
3/4-10-EMT	3/4	21	0.922	23.42	0.049	1.25	46	20.9	2100	5000	500	837654107676
1-10-EMT	1	27	1.163	29.54	0.057	1.45	67	30.4	3050	3000	300	837654107683
1-1/4-10-EMT	1-1/4	35	1.51	38.35	0.065	1.65	101	45.8	4580	2000	200	837654107690
1-1/2-10-EMT	1-1/2	41	1.74	44.20	0.065	1.65	116	52.6	5250	1500	150	837654107706
2-10-EMT	2	53	2.197	55.80	0.065	1.65	148	67.1	6710	1200	120	837654107713
2-1/2-10-EMT	2-1/2	63	2.875	73.03	0.072	1.83	216	98	9790	610	61	837654107720
3-10-EMT	3	78	3.5	88.90	0.072	1.83	263	119.3	11930	510	51	837654107737
3-1/2-10-EMT	3-1/2	91	4	101.60	0.083	2.11	349	158.3	15800	370	37	837654107744
4-10-EMT	4	103	4.5	114.30	0.083	2.11	393	178.2	17810	300	30	837654107751

OUTSIDE DIAMETER TOLERANCES

+/- .005 in. (.13mm) for trade sizes 1/2" (16mm) through 2" (53mm), +/- .010 in. (.25mm) for trade sizes 2-1/2" (63mm) +/- .015 in. (.38mm) for trade size 3" (78mm), +/- .020 in. (.51mm) for trade sizes 3-1/2" (91mm) and 4" (103mm) NOTE: Length = 10 ft. (3.05m) with a tolerance of +/- .25" (6.35 mm)

• EASY AND ACCURATE BENDING

Processed by high frequency induction welding to prevent cracking when bend

• EASY WIRE PUSHING AND PULLING

Inside welding removed, and with the grey color epoxy resin coating

• HIGH CORROSION RESISTANCE

Pure zinc coating on the exterior wall with clear anti-corrosion coating finish



ELECTRICAL CONDUIT AND WIRES



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302
 PHONE : (718).338.1851 FAX : (718).228.1851
 orders@ammoelectric.com

www.ammoelectric.com