



Company: _____

Job: _____ #Item: _____

Notes: _____

Intermediate Metal Conduit (Imc)



The length of straight conduit, and the weight of finished zinc-coated conduit or bare threaded tube to be coated with an alternate corrosion-resistant coating with one coupling

AMMO#	TRADE SIZE		NOMINAL OD		WALL THICK.A		APROX 100FTAP		WEIGHT (kg)	PKG		UPC
	US	METRIC	in	mm	in	mm	lbs	kg		FT	PCS	
1/2-10-IMC	1/2	16	0.815	20.7	0.078	1.98	61.46	27.88	3.064	3500	350	837654107768
3/4-10-IMC	3/4	21	1.029	26.13	0.083	2.1	83.58	37.91	3.810	2500	250	837654107775
1-10-IMC	1	27	1.29	32.76	0.093	2.35	118.66	53.82	5.240	1700	170	837654107782
1-1/4-10-IMC	1-1/4	35	1.638	41.61	0.095	2.42	157.23	71.32	6.810	1350	135	837654107799
1-1/2-10-IMC	1-1/2	41	1.883	47.82	0.1	2.54	190.64	86.47	8.798	1100	110	837654107805
2-10-IMC	2	53	2.36	59.94	0.105	2.67	253.39	114.94	10.850	800	80	837654107812
2-1/2-10-IMC	2-1/2	63	2.857	72.56	0.15	3.81	434.62	197.14	20.293	370	37	837654107829
3-10-IMC	3	78	3.476	88.29	0.15	3.81	533.81	242.13	25.053	300	30	837654107836
3-1/2-10-IMC	3-1/2	91	3.971	100.86	0.15	3.81	613.42	278.24	28.500	240	24	837654107843
4-10-IMC	4	103	4.466	113.43	0.15	3.81	692.39	314.06	32.960	240	24	837654107850

• EASY AND ACCURATE BENDING

High strength ductile steel for long life

• EASY WIRE PUSHING AND PULLING

Provides smooth, continuous raceways for fast wire-pulling

• HIGH CORROSION RESISTANCE

High corrosion resistance
Hot-dip galvanized outside and inside, inhibit white rust and increase corrosion resistance



STANDARD: UL 1242 & ANSI C80.6

OUTSIDE DIAMETER TOLERANCES

NOTE: Length = 10 ft. (3.05m) with a tolerance of a +/- .25" (6.35mm)

+/- .005 in. (.13mm) for trade sizes 1/2" (16mm) through 1" (25mm)

+/- .010 in (.25mm) for trade sizes 2-1/2" (63mm) through 4" (103mm)

+/- .0075 in. (19 mm) for trade sizes 1-1/4" (36mm) through 2" (53mm)

ELECTRICAL CONDUIT AND WIRES