



CATEGORY  
**ELECTRICAL  
 CONDUIT**  
 AMMO ITEM #

**LT-100/50UL**

Company: \_\_\_\_\_  
 Job: \_\_\_\_\_ #Item: \_\_\_\_\_  
 Notes: \_\_\_\_\_

# Liquid Tight Non-Metallic Tubing



## APPLICATIONS

- Use at commercial and industry environment
- Machinevev, hew equipment

## FEATURES

- High temperature condition
- Use at wet, dry and oilless condition
- Out door, UV resistant
- Straight inbuilt (bury)
- Surface smooth
- Reinforce PVC, enhance the structure

## MATERIAL

PVC

## TEMPERATURE SPECIFICATION

- 80°C Dry
- 60°C Wet
- 70°C Oil



AMMO#	SIZE	ID (mm)		OD (mm)		WEIGHT (kg)	PKG (m)	UPC
		MIN	MAX	MIN	MAX			
<b>38LT100UL</b>	3/8"	12.29	12.8	17.53	18.03	5.2	30.5	837654120453
<b>12LT100UL</b>	1/2"	15.8	16.31	20.83	21.34	6.2	30.5	837654120460
<b>34LT100UL</b>	3/4"	20.83	21.34	26.16	26.67	8.4	30.5	837654120477
<b>1LT100UL</b>	1"	26.44	27.08	32.77	33.4	12.2	30.5	837654120484
<b>125LT50UL</b>	1-1/4"	35.05	35.81	41.4	42.13	8.0	30.5	837654120491
<b>150LT50UL</b>	1-1/2"	40.01	40.64	47.37	48.23	11.0	30.5	837654120507
<b>2LT50UL</b>	2"	51.31	51.94	59.44	60.33	15.5	15.3	837654120514

## ELECTRICAL CONDUIT



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302  
 PHONE : (718).338.1851 FAX : (718).228.1851  
 orders@ammoelectric.com

[www.ammoelectric.com](http://www.ammoelectric.com)