



CATEGORY

WIRING  
DEVICES

AMMO ITEM #

TR15-DHG-WH

Company: \_\_\_\_\_

Job: \_\_\_\_\_ #Item: \_\_\_\_\_

Notes: \_\_\_\_\_

# Duplex Receptacle Hospital Grade, Back & Side Wired



## APPLICATION

Hospital applications

## FEATURES

Decorator Tamper Resistent Receptacles

## CONFIGURATION

- Wire Type: \_\_\_\_\_ Copper only
- Wire Binding screws: \_\_\_\_\_ UL498: Minimum Dia#8(.164)  
Max Threads/inch = 32
- Yoke: \_\_\_\_\_ Brass
- Rated Output Current: \_\_\_\_\_ 15 A (min)
- Rated Voltage: \_\_\_\_\_ 125 V
- Nema: \_\_\_\_\_ 5-15R

## SCREW TERMINALS

- (x4) #14-#12 AWG Solid, on hot, neutral terminals
- (x1) #14-#12 AWG Solid, on Ground terminals
- Hot terminal - Yellow, Neutral - White, Ground - Green
- Screw Torque: \_\_\_\_\_ minimum 20lbf-in without stripping of threads

## CERTIFICATION

- UL498
- CSA Standards

## MATERIAL

- Upper cover: \_\_\_\_\_ PC
- Base: \_\_\_\_\_ PC
- Protection cover: \_\_\_\_\_ PA
- Connection screw: \_\_\_\_\_ Steel (plating)
- Clamps parts: \_\_\_\_\_ Copper o plated aluminum

## COLOR

White

## PACKAGING

- Inner: \_\_\_\_\_ 10
- Master: \_\_\_\_\_ 100
- UPC number: \_\_\_\_\_ 837654093184



## WIRING & DEVICES



1000 COMMERCE CENTER DR ELKTON MD 21921  
PHONE : (718).338.1851 FAX : (718).228.1851  
orders@ammoelectric.com

www.ammoelectric.com