



CATEGORY

**ELECTRICAL
FITTINGS**

AMMO ITEM #

ARCCNZ-I

Company: _____

Job: _____ #Item: _____

Notes: _____

Connector Compression Insulated

**APPLICATION**

Used to secure and terminate steel EMT conduit to knock-outs in concrete-tight box, dry or damp location applications concrete-tight

MATERIAL

Zinc die casting

FINISH

Polishing



AMMO#	SIZE	HIGHT (mm)	INSIDE DIA (mm)	OUTSIDE DIE (mm)	HEAD INSIDE (mm)	WEIGHT (g)	PKG	UPC
ARCCNZ-50I	1/2"	29.42	17.94	34.52	15.40	29.7	500	837654067987
ARCCNZ-75I	3/4"	32.87	23.43	37.50	20.35	48.4	250	837654067994
ARCCNZ-100I	1"	31.60	29.55	46.10	25.85	72.7	200	837654068007
ARCCNZ-125I	1-1/4"	44.60	38.38	55.60	34.60	122.4	25	837654068014
ARCCNZ-150I	1-1/2"	46.80	44.20	62.80	40.50	165.2	25	837654068021
ARCCNZ-200I	2"	55.20	55.81	78.50	52.00	234.5	20	837654068038
ARCCNZ-250I	2-1/2"	83.02	73.91	95.65	68.25	491.6	12	837654068045
ARCCNZ-300I	3"	92.40	89.92	118.90	83.55	607.5	12	837654067963
ARCCNZ-350I	3-1/2"	93.50	102.74	130.93	94.50	821.0	10	837654088135
ARCCNZ-400I	4"	96.80	115.44	145.38	106.55	916.6	6	837654068069

ELECTRICAL FITTINGS



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302
PHONE : (718).338.1851 FAX : (718).228.1851
orders@ammoelectric.com

www.ammoelectric.com