



CATEGORY

NEC (Nipples, Elbows & Couplings)

AMMO ITEM #

ARAC

Company: _____

Job: _____ #Item: _____

Notes: _____

Alumium Coupling



APPLICATION

Threaded couplings are used to join two lengths of threaded Rigid Alum Conduit

FEATURES


- Light Weight Rigid Aluminum Coupling is approximately one-third the weight of steel
- Corrosion Resistant Aluminum resists most corrosive atmospheres in industrial environments

MATERIAL / FINISH

- Alum 6063 T5
- Natural

CERTIFICATIONS

- UL Standard: 6A
- Fed. Spec. WW-C-540C



AMMO#	SIZE	A (in)	B (in)	C (in)	WEIGHT (g)	PKG	UPC
ARAC-50	1/2"	1.626	1.079	1/2" - 14 NPSL	28	150	837654120897
ARAC-75	3/4"	1.642	1.327	3/4" - 14 NPSL	41	50	837654120903
ARAC-100	1"	1.969	1.563	1" - 11.5 NPSL	56	30	837654120910
ARAC-125	1-1/4"	2.031	1.953	1-1/4" - 11.5 NPSL	81	25	837654120927
ARAC-150	1-1/2"	2.063	2.220	1-1/2" - 11.5 NPSL	103	25	837654120934
ARAC-200	2"	2.126	2.748	2" - 11.5 NPSL	153	20	837654120941
ARAC-250	2-1/2"	3.189	3.280	2-1/2" - 8 NPSL	156	12	8837654120958
ARAC-300	3"	3.311	3.969	3" - 8 NPSL	285	8	837654120965
ARAC-350	3-1/2"	3.406	4.437	3-1/2" - 8 NPSL	464	4	837654120972
ARAC-400	4"	3.516	5.000	4" - 8 NPSL	615	4	837654120989

NEC (Nipples, Elbows & Couplings)



400 MARTIN LUTHER KING JR WAY, BRIDGETON, NJ 08302
 PHONE : (718).338.1851 FAX : (718).228.1851
 orders@ammoelectric.com

www.ammoelectric.com