



CATEGORY

**ELECTRICAL
FITTINGS**

AMMO ITEM #

ARBU-MI

Company: _____

Job: _____ #Item: _____

Notes: _____

Conduit Bushings Insulated



APPLICATIONS

- Used with locknut to terminate threaded rigid conduit or IMC to a box or enclosure
- Rounded surface of bushing prevents damage to wire insulation

FEATURES


- The plastic liner won't chip, crack, swell or shrink. It resists corrosion, chemicals and temperature extremes
- Provide a smooth pulling surface
- RoHS compliant

MATERIALS

- Body: malleable iron
- Throat: PP Rate at 105°
- Lug: Alum

FINISHES

- Malleable iron – HDG and Zinc plated
- PE, PP, Alum – natural



AMMO#	SIZE	A (in)	B (in)	WEIGHT (lb)	INNER	MASTER	UPC
ARBU-50MI	1/2"	1.102	0.587	0.049	100	1000	840526223060
ARBU-75MI	3/4"	1.354	0.587	0.068	100	1000	840526223077
ARBU-100MI	1"	1.642	0.669	0.095	50	500	840526223084
ARBU-125MI	1-1/4"	1.945	0.724	1.323	25	250	840526223091
ARBU-150MI	1-1/2"	2.213	0.748	1.676	25	250	840526223107
ARBU-200MI	2"	2.717	0.748	0.220	10	100	840526223114
ARBU-250MI	2-1/2"	3.268	0.961	0.406	10	100	840526223121
ARBU-300MI	3"	3.980	0.965	0.500	10	100	840526223138
ARBU-350MI	3-1/2"	4.461	0.969	0.595	-	10	840526223145
ARBU-400MI	4"	4.961	0.965	0.637	-	10	840526223152
ARBU-500MI	5"	6.130	1.161	1.190	-	10	840526223169
ARBU-600MI	6"	7.394	1.260	1.653	-	10	840526223176

ELECTRICAL FITTINGS



1000 COMMERCE CENTER DR ELKTON MD 21921
 PHONE : (718).338.1851 FAX : (718).228.1851
 orders@ammoelectric.com

www.ammoelectric.com