



CATEGORY

**ELECTRICAL  
FITTINGS**

AMMO ITEM #

**ARCCPLT**

Company: \_\_\_\_\_  
Job: \_\_\_\_\_ #Item: \_\_\_\_\_  
Notes: \_\_\_\_\_

## Combination Coupling Liquidtight to Rigid



### Combination Coupling - Rigid or IMC to Liquidtight Conduit

#### APPLICATIONS

- Used to join threaded Rigid conduit or IMC to liquid tight metallic conduit (LFMC)
- Liquid-tight rated

#### FEATURES


- Connectors have a unique long ferrule with more pronounced threads that provide maximum surface contact for better sealing and a continuous, permanent, positive metal-to-metal ground
- Liquidtight / raintight / oiltight / concretetight
- Suitable for wet locations
- Full, machined tapered threads (NPT)

#### MATERIALS

- Body: zinc plated steel
- Gland: PE
- Compression Nut: zinc plated steel
- Ferrule: zinc plated steel

#### CERTIFICATIONS

- UL-514B
- CSA Standard C22.2 No. 18.3-12



| AMMO#       | SIZE   | A<br>(in) | B<br>(in) | WEIGHT<br>(lb) | INNER | MASTER | UPC          |
|-------------|--------|-----------|-----------|----------------|-------|--------|--------------|
| ARCCPLT-38  | 3/8"   | 1.10      | 1.78      | 0.156          | 20    | 200    | 837654109564 |
| ARCCPLT-50  | 1/2"   | 1.17      | 1.78      | 0.143          | 20    | 200    | 837654109571 |
| ARCCPLT-75  | 3/4"   | 1.43      | 1.94      | 0.219          | 10    | 100    | 837654109588 |
| ARCCPLT-100 | 1"     | 1.76      | 2.19      | 0.366          | 5     | 50     | 837654109595 |
| ARCCPLT-125 | 1-1/4" | 2.16      | 2.23      | 0.539          | 5     | 50     | 837654109601 |
| ARCCPLT-150 | 1-1/2" | 2.38      | 2.62      | 0.643          | -     | 12     | 837654109618 |
| ARCCPLT-200 | 2"     | 2.87      | 2.67      | 0.896          | -     | 5      | 837654109625 |

## ELECTRICAL FITTINGS



1000 COMMERCE CENTER DR ELKTON MD 21921  
PHONE : (718).338.1851 FAX : (718).228.1851  
orders@ammoelectric.com

[www.ammoelectric.com](http://www.ammoelectric.com)