



CATEGORY

ELECTRICAL
FITTINGS

AMMO ITEM #

ARCD350

Company: _____

Job: _____ #Item: _____

Notes: _____

BLK Insulated Connector Dual



APPLICATION

- All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
- One input & multiple output configurations, the allowable ampacities per NEC Table 310.16 and 310.17 are as follows: #4-95 Amp, 1/0-170 Amp, 3/0-225 Amp, 250-290 Amp, 350-350 Amp, 600-475 Amp, 750-535 Amp
- For multiple inputs, the inputs must be staggered

FEATURES

- Flexibility in the field
- Ensures reliability
- Application variability
- Chemical resistant
- Entry port closure
- Prevents oxide formation
- 90 °C - 600 V

MATERIALS

- Body: _____ 6061-T6 aluminum
- Insulating sleeve: _____ PVC
- Conector type: _____ both aluminum and copper

SPECIFICATIONS

- Broad wire range: _____ 750 kcmil - 14
- Environmental temperature: _____ 10°C - 90°C
- Voltage withstand: _____ 2500 Vac/1Min
- Terminal: _____ alinum oxidation
- Number of wires connected: _____ one wire per terminal
- UL Listed: _____ CU9AL



SUITABLE FOR USE ON THE LINE SIDE OF SERVICE EQUIPMENS

AMMO#	WIRE RANGE	PORTS	HEX SIZE	STRIP LENGTH (in)	LENGTH (in)	WIDTH (in)	HEIGHT (in)	INNER	MASTER	UPC
ARCD350-1	350#-#6	Inline Splice	3/8"	1.843	4.84	2.59	1.47	4	32	840526226467
ARCD350-2	350#-#6	2	3/8"	1.732	2.52	2.60	2.34	4	32	840526226313
ARCD350-3	350#-#6	3	3/8"	1.843	3.52	2.64	2.29	6	24	840526226320
ARCD350-4	350#-#6	4	3/8"	1.843	4.55	2.60	2.60	4	16	840526226337
ARCD350-5	350#-#6	5	3/8"	1.843	4.90	2.60	2.60	4	16	840526226344
ARCD350-6	350#-#6	6	3/8"	1.843	5.95	2.60	2.60	3	9	840526226351
ARCD350-7	350#-#6	7	3/8"	1.843	7.00	2.60	2.60	3	9	840526226368
ARCD350-8	350#-#6	8	3/8"	1.843	8.06	2.60	2.60	3	9	840526226375
ARCD350-9	350#-#6	9	3/8"	1.843	9.11	2.60	2.60	3	6	840526226382
ARCD350-10	350#-#6	10	3/8"	1.843	10.16	2.60	2.60	3	6	840526226399
ARCD350-11	350#-#6	11	3/8"	1.843	11.21	2.60	2.60	3	6	840526226405
ARCD350-12	350#-#6	12	3/8"	1.843	12.26	2.60	2.60	3	6	840526226474

ELECTRICAL FITTINGS



1000 COMMERCE CENTER DR ELKTON MD 21921
 PHONE : (718).338.1851 FAX : (718).228.1851
 orders@ammoelectric.com

www.ammoelectric.com