



CATEGORY
**ELECTRICAL
 FITTINGS**
 AMMO ITEM #
ARGB-I

Company: _____
 Job: _____ #Item: _____
 Notes: _____

Insulated Grounding Bushing



APPLICATIONS



- Suitable for use in various environments (aluminum lug)
- For securing service conduit to an enclosure with a locknut
- Includes lug for connecting a bonding jumper to a neutral bus bar
- Rounded bushing design protects wire insulation
- Plastic liner safeguards wire insulation

FEATURE

Liner is rated flame retardant to 105°C

MATERIALS

- Body: malleable iron
- Plastic insulator
- Lug: aluminum
- Clamping screw: steel
- Set screws: steel



AMMO#	THREAD HOLE	A (in)	B (in)	C (in)	GROUNDING LUG SIZE		WIRE RANGE	WEIGHT (lb)	INNER	MASTER	UPC
					MIN	MAX					
ARGB-50I	1/2"	1.05	0.55	0.75	14	4	4 AWG - 8 AWG	0.05	50	500	840526222544
ARGB-75I	3/4"	1.26	0.74	0.75	14	4	4 AWG - 8 AWG	0.07	50	500	840526222551
ARGB-100I	1"	1.6	0.97	0.75	14	4	4 AWG - 8 AWG	0.10	25	250	840526222568
ARGB-125I	1-1/4"	1.95	1.28	0.75	14	4	4 AWG - 8 AWG	0.15	20	200	840526222575
ARGB-150I	1-1/2"	2.12	1.49	0.75	14	4	4 AWG - 6 AWG	0.16	10	100	840526222582
ARGB-200I	2"	2.66	1.81	0.75	14	4	4 AWG	0.24	10	50	840526222599
ARGB-250I	2-1/2"	3.15	2.3	1.13	14	1/0	2/0 AWG - 2 AWG	0.40	-	50	840526222605
ARGB-300I	3"	3.81	2.83	1.13	14	1/0	2/0 AWG - 1/0 AWG	0.49	-	25	840526222612
ARGB-350I	3-1/2"	4.25	3.36	1.13	14	1/0	2/0 AWG	0.55	-	10	840526222629
ARGB-400I	4"	4.86	3.83	1.13	14	1/0	2/0 AWG	0.64	-	10	840526222636

ELECTRICAL FITTINGS



1000 COMMERCE CENTER DR ELKTON MD 21921
 PHONE : (718).338.1851 FAX : (718).228.1851
 orders@ammoelectric.com

www.ammoelectric.com