



CATEGORY

**ELECTRICAL
FITTINGS**

AMMO ITEM #

ARGBU-MHDG

Company: _____

Job: _____ #Item: _____

Notes: _____

Insulated Grounding Bushings



APPLICATIONS

- Use to provide a means of grounding Rigid or IMC conduit
- Indoor or outdoor use (aluminum lug)
- Use with locknut to terminate service conduit to a cabinet
- Lug provided for bonding jumper to a neutral bus bar
- Round surface of bushing prevents damage to wire insulation
- Plastic liner prevents damage to wire insulation

FEATURES

- Hot dip galvanized for superior protection against corrosion
- Tin plated aluminum alloy 6061-T6 rated for AL and CU conductor
- Liner is rated flame retardant to 105°C
- UL listed for use with copper or aluminum grounding conductor

MATERIALS


- Body: malleable iron
- Plastic insulator
- Lug: aluminum
- Clamping screw: steel
- Set screws: steel

CERTIFICATIONS

- UL Standard: UL 514B & UL 467
- RoHS
- Fed. Spec: A-A-50553
- NEMA: FB 1

FINISH

Hot dip galvanized



AMMO#	SIZE	A (in)	B (in)	GROUNDING LUG SIZE		WEIGHT (lb)	INNER	MASTER	UPC
				MIN	MAX				
ARGBU-50MHDG	1/2"	1.08	.57	14	4	0.30	50	500	837654112113
ARGBU-75MHDG	3/4"	1.31	.57	14	4	0.41	50	500	837654112120
ARGBU-100MHDG	1"	1.61	.65	14	4	0.58	25	250	837654112137
ARGBU-125MHDG	1-1/4"	1.91	.71	14	4	0.57	20	200	837654112144
ARGBU-150MHDG	1-1/2"	2.16	.73	14	4	0.66	10	100	837654112151
ARGBU-200MHDG	2"	2.72	.73	14	4	0.86	10	100	837654112168
ARGBU-250MHDG	2-1/2"	3.23	.94	14	1/0	1.54	5	50	837654112175
ARGBU-300MHDG	3"	3.88	.94	14	1/0	2.86	-	25	837654112182
ARGBU-350MHDG	3-1/2"	4.43	.94	14	1/0	7.94	-	10	837654112199
ARGBU-400MHDG	4"	4.89	.94	14	1/0	9.52	-	10	837654112205

ELECTRICAL FITTINGS



1000 COMMERCE CENTER DR ELKTON MD 21921
 PHONE : (718).338.1851 FAX : (718).228.1851
 orders@ammoelectric.com

www.ammoelectric.com