



CATEGORY
ELECTRICAL
FITTINGS
AMMO ITEM #
ARHBT

Company: _____

Job: _____ #Item: _____

Notes: _____

Black Hole Cable Tie



Nylon cable ties with mountable head

APPLICATION

Wrap the cable and fix with screw

FEATURES

- Operation temperature -40° F to +185° F
- Minimum installation temperature 14° F
- UL94 V-2 flammability, and UV resistant

MATERIAL

Nylon PA66

CERTIFICATIONS

- Rohs
- UL



AMMO#	SIZE (in)	SCREW HOLE SIZE	TENSILE STRENGTH	MIN / MAX BUNDLE DIAMETER	WEIGHT (lb)	PKG	UPC
ARHBT04-100	4 x 0.984	0.130 - 0.138 in	80 N	0.12 - 0.75 in	0.0009	100	837654113127
ARHBT04-1000	4 x 0.984	0.130 - 0.138 in	80 N	0.12 - 0.75 in	0.0009	1000	837654113134
ARHBT06-100	6 x 1.417	0.134 - 0.142 in	180 N	0.12 - 1.40 in	0.0018	100	837654113141
ARHBT06-1000	6 x 1.417	0.134 - 0.142 in	180 N	0.12 - 1.40 in	0.0018	1000	837654113158
ARHBT07-100	7 x 0.181	0.156 - 0.164 in	222 N	0.12 - 1.45 in	0.0024	100	837654113165
ARHBT07-1000	7 x 0.181	0.156 - 0.164 in	222 N	0.12 - 1.45 in	0.0024	1000	837654113172
ARHBT08-100	8 x 0.181	0.156 - 0.164 in	222 N	0.12 - 1.96 in	0.0029	100	837654113189
ARHBT08-1000	8 x 0.181	0.156 - 0.164 in	222 N	0.12 - 1.96 in	0.0029	1000	837654113196
ARHBT11-100	11 x 0.181	0.156 - 0.164 in	222 N	0.12 - 3.26 in	0.0043	100	837654113202
ARHBT11-1000	11 x 0.181	0.156 - 0.164 in	222 N	0.12 - 3.26 in	0.0043	1000	837654113219
ARHBT14-100	14 x 0.181	0.156 - 0.164 in	222 N	0.12 - 4.09 in	0.0053	100	837654113226
ARHBT14-1000	14 x 0.181	0.156 - 0.164 in	222 N	0.12 - 4.09 in	0.0053	1000	837654113233
ARHBT18-100	18 x 2.992	0.211 - 0.220 in	540 N	0.31 - 4.30 in	0.0154	100	837654113240
ARHBT18-1000	18 x 2.992	0.211 - 0.220 in	540 N	0.31 - 4.30 in	0.0154	1000	837654113257

ELECTRICAL FITTINGS



1000 COMMERCE CENTER DR ELKTON MD 21921
PHONE : (718).338.1851 FAX : (718).228.1851
orders@ammoelectric.com

www.ammoelectric.com