



CATEGORY
**ELECTRICAL
 FITTINGS**
 AMMO ITEM #
ARLNS

Company: _____
 Job: _____ #Item: _____
 Notes: _____

Conduit Locknuts



APPLICATIONS

- Insulated zinc die casting grounding bushings are used on the end of rigid and IMC conduits and other threaded connectors to provide a smooth well rounded bearing surface to protect wires or cables
- Providing a means to connect a grounding conductor
- Nylon Liner Rated 150° C
- Used to secure threaded conduits or connectors to electrical junction boxes

FEATURE


Use for IMC/ Rigid conduit

MATERIAL/FINISH

- Zinc plated steel
- Electro-Gal

CERTIFICATIONS

- UL Standard: 514B
- CSA Standard: C22.2 No. 18



AMMO#	SIZE	THREAD PITCH DIAMETER	A (in)	B (in)	WEIGHT (lb)	INNER	MASTER	UPC
ARLNS-50	1/2"	.787 - .797	1.15	.11	0.009	200	2000	840526224302
ARLNS-75	3/4"	.999 - 1.009	1.45	.115	0.013	100	1000	840526224319
ARLNS-100	1"	1.25 - 1.26	1.75	.14	0.023	100	1000	840526224326
ARLNS-125	1-1/4"	1.595 - 1.605	2.10	.14	0.040	50	500	840526224333
ARLNS-150	1-1/2"	1.837 - 1.847	2.40	.14	0.046	50	500	840526224340
ARLNS-200	2"	2.307 - 2.317	2.95	.14	0.062	25	250	840526224357
ARLNS-250	2-1/2"	2.777 - 2.788	3.55	.185	0.135	-	50	840526224364
ARLNS-300	3"	3.403 - 3.414	3.55	.19	0.183	-	50	840526224371
ARLNS-350	3-1/2"	3.892 - 3.904	4.20	.19	0.240	-	25	840526224388
ARLNS-400	4"	4.399 - 4.411	4.75	.19	0.999	-	25	840526224395

ELECTRICAL FITTINGS



Ammo Electric Inc.

1000 COMMERCE CENTER DR ELKTON MD 21921
 PHONE : (718).338.1851 FAX : (718).228.1851
 orders@ammoelectric.com

www.ammoelectric.com