



CATEGORY

**ELECTRICAL
FITTINGS**

AMMO ITEM #

ARLTCN-I

Company: _____

Job: _____ #Item: _____

Notes: _____

Straight Liquid Tight Connector Insulated



APPLICATIONS

- To secure, ground and seal liquid-tight flexible metal conduit to boxes and enclosures
- Connects conduit and terminates bonding conductor run externally across liquid-tight conduit

FEATURES

- Tapered threaded male hub NPT
- Compact, slim diameter with small turning radius
- Furnished with an insulated throat with steel locknut and sealing ring
- Suitable for wet locations
- Long ferrule prevents pullout and tight bend conduit "pop-out"
- RoHS compliant

MATERIAL


Steel locknut

CERTIFICATIONS

- UL Standards: 514B
- CUL Standard: C22.2 No.18.3-12
- Fed. Spec. W-F-408E
- NEMA: FB-1

FINISHES

- Electro zinc plated and chromate coated
- Steel - electro zinc plated and chromate coated
- PE, PP, Alum - natural



AMMO#	SIZE	A (in)	B (in)	C (in)	WEIGHT (lb)	INNER	MASTER	UPC
ARLTCN-38I	3/8 1/2" KO	0.917	0.531	1.220	0.11	20	200	840526220830
ARLTCN-50I	1/2"	0.925	0.535	1.339	0.12	20	200	840526220847
ARLTCN-75I	3/4"	1.008	0.591	1.602	0.15	10	100	840526220854
ARLTCN-100I	1"	1.083	0.543	1.795	0.23	5	50	840526220861
ARLTCN-125I	1-1/4"	1.224	0.673	2.402	0.44	5	50	840526220878
ARLTCN-150I	1-1/2"	1.244	0.701	2.638	0.52	2	20	840526220885
ARLTCN-200I	2"	1.453	0.709	3.181	0.66	2	20	840526220892

ELECTRICAL FITTINGS



1000 COMMERCE CENTER DR ELKTON MD 21921
 PHONE : (718).338.1851 FAX : (718).228.1851
 orders@ammoelectric.com

www.ammoelectric.com