



CATEGORY

ELECTRICAL
FITTINGS

AMMO ITEM #

ARLTGN-MI

Company: _____

Job: _____ #Item: _____

Notes: _____

Liquid Tight Straight Ground Connector Malleable Iron



APPLICATIONS

- To secure, ground and seal liquid-tight flexible metal conduit to boxes and enclosures
- Connects conduit and terminates bonding conductor run externally across liquid-tight conduit

FEATURES

- Tapered threaded male hub NPT
- Compact, slim diameter with small turning radius
- Furnished with an insulated throat with steel locknut and sealing ring
- Suitable for wet locations
- Long ferrule prevents pullout and tight bend conduit "pop-out"
- RoHS compliant

MATERIALS


- Malleable iron
- Steel locknut

CERTIFICATIONS

- UL Standards: 514B
- CUL Standard: C22.2 No.18.3-12
- Fed. Spec. W-F-408E
- NEMA: FB-1

FINISHES

- Malleable iron - electro zinc plated and chromate coated
- Steel - electro zinc plated and chromate coated
- PE, PP, Alum - natural



AMMO#	SIZE	A (in)	B (in)	C (in)	LUG SIZE	WEIGHT (lb)	INNER	MASTER	UPC
ARLTGN-38MI	3/8"	0.917	0.531	1.220	4-14	0.18	10	100	837654104170
ARLTGN-50MI	1/2"	0.925	0.535	1.339	4-14	0.19	10	100	837654104187
ARLTGN-75MI	3/4"	1.008	0.591	1.602	4-14	0.26	5	50	837654104194
ARLTGN-100MI	1"	1.083	0.543	1.795	4-14	0.39	5	50	837654104200
ARLTGN-125MI	1-1/4"	1.224	0.673	2.402	4-14	0.56	2	20	837654104217
ARLTGN-150MI	1-1/2"	1.244	0.701	2.638	4-14	0.84	2	20	837654104224
ARLTGN-200MI	2"	1.453	0.709	3.181	4-14	1.11	2	20	837654104231
ARLTGN-250MI	2-1/2"	1.929	1.087	3.843	1/0-8	2.23	-	1	837654104248
ARLTGN-300MI	3"	2.079	1.114	4.701	1/0-8	3.21	-	1	837654104255
ARLTGN-350MI	3-1/2"	2.031	1.134	5.252	3/0-6	3.93	-	1	837654104262
ARLTGN-400MI	4"	2.228	1.150	6.472	3/0-6	4.85	-	1	837654104279

ELECTRICAL FITTINGS



1000 COMMERCE CENTER DR ELKTON MD 21921
PHONE : (718).338.1851 FAX : (718).228.1851
orders@ammoelectric.com

www.ammoelectric.com