



CATEGORY
**ELECTRICAL
FITTINGS**

AMMO ITEM #

ARLTGN90-MI

Company: _____

Job: _____ #Item: _____

Notes: _____

90° Liquid Tight Ground Connector Malleable Iron



APPLICATIONS

- To secure, ground and seal liquid-tight flexible metal conduit to boxes and enclosures
- Connects conduit and terminates bonding conductor run externally across liquid-tight conduit

FEATURES

- Tapered threaded male hub NPT
- Compact, slim diameter with small turning radius
- Furnished with an insulated throat with steel locknut and sealing ring
- Suitable for wet locations
- Long ferrule prevents pullout and tight bend conduit "pop-out"
- RoHS compliant

MATERIALS


- Malleable iron
- Steel locknut

CERTIFICATIONS

- UL Standards: 514B
- CUL Standard: C22.2 No.18.3-12
- Fed. Spec. W-F-408E
- NEMA: FB-1

FINISHES

- Malleable iron - electro zinc plated and chromate coated
- Steel - electro zinc plated and chromate coated
- PE, PP, Alum - natural



AMMO#	SIZE	A (in)	B (in)	C (in)	LUG SIZE	WEIGHT (lb)	INNER	MASTER	UPC
ARLTGN90-38MI	3/8"	2.541	0.536	1.120	4 - 14	0.27	5	50	840526221516
ARLTGN90-50MI	1/2"	2.749	0.543	1.241	4 - 14	0.30	5	50	840526221523
ARLTGN90-75MI	3/4"	2.977	0.58	1.503	4 - 14	0.43	2	20	840526221530
ARLTGN90-100MI	1"	3.644	0.675	1.763	4 - 14	0.66	2	20	840526221547
ARLTGN90-125MI	1-1/4"	4.138	0.695	2.248	4 - 14	1.06	2	20	840526221554
ARLTGN90-150MI	1-1/2"	4.635	0.694	2.471	4 - 14	1.16	2	20	840526221561
ARLTGN90-200MI	2"	5.347	0.729	3.007	4 - 14	1.84	2	20	840526221578
ARLTGN90-250MI	2-1/2"	8.217	1.056	3.654	1/0 - 8	4.67	-	1	840526221585
ARLTGN90-300MI	3"	9.180	1.104	4.471	1/0 - 8	6.39	-	1	840526221592
ARLTGN90-350MI	3-1/2"	9.871	1.163	4.942	3/0 - 6	9.00	-	1	840526221608
ARLTGN90-400MI	4"	10.757	1.155	5.501	3/0 - 6	10.1	-	1	840526221615

ELECTRICAL FITTINGS



1000 COMMERCE CENTER DR ELKTON MD 21921
PHONE : (718).338.1851 FAX : (718).228.1851
orders@ammoelectric.com

www.ammoelectric.com